



Specifications

Key Features

Slim front bezel
Height-adjustable
Right / left swivel
Multimedia

Monitor Cosmetics

Silver finished bezel / black cabinet

LCD

19" active matrix, thin-film-transistor (TFT)

Pixel Pitch

0.294(H) x 0.294(V)

Max. Resolution

SXGA 1280 x 1024

Scan Frequency

Horizontal: 24kHz - 85kHz
Vertical: 50Hz - 85Hz

View Angle

Horizontal: 170°
Vertical: 170°

Display Area (mm)

376.32(H) x 301.056(V)

Display Colour

16.7 million

Contrast Ratio

500:1

Brightness

250 cd/m²

Response Time (Tr+Tf)

25 ms

Compatibility

Windows 95/98/98SE/Me/NT4/2000/XP
Mac OS, Macintosh
Plug & Play - DDC 2B

Input Video Signal (Connector: 15 pin D-sub)

Analogue 0.7 Vp-p separate sync.
TTL level, RGB analogue

Input Power Source:

AC 100-240V, 50-60Hz

Power Management

Normal operation: < 55 W
Off/Suspend/Stand-by mode: < 5 W

Operation Environment

Temperature: 0 - 40°C
Humidity: 20% - 80%

Analogue RSB OSD

Brightness, Contrast, Black level, Volume, Mute,
Clock, Clock Phase H-position, V-position,
Auto Set-up, Adjust, Balance, All reset,
OSD position, Power save, Language,
Display mode, Colour

Control Button

Power, Auto, ▼ OSD / Main menu,
▶ OSD / Sub menu, Minus, Plus, Exit

Tilt Angle

Max. forward tilt: 3°
Max. backward tilt: 25°

Swivel

Right / left: 25°

Cabinet dimensions (W x D x H)

Net: 434 x 204 x 426 mm
Gross: 510 x 276 x 492 mm

Weight

Net: 7.0kg
Gross: 9.5kg

Regulation safety & EMI

FCC class B, CE, UL/cUL,
TUV/GS, Energy Star, TCO 95

Warranty

Three year on-site exchange

GNR Corporation Ltd

Unit 3, Newmarket Court, Kingston, Milton Keynes, MK10 0AG
Tel.: +44 (0)870 1280 880 / Fax: +44 (0)870 1280 878 / E-mail: info@gnrintl.com
www.gnrintl.com