

F173

17" TFT LCD Monitor



Specifications

Key Features

Modern outlook & slim lightweight design
Solid steel stand
Integrated power supply
Glossy high impact retail packaging

Monitor Cosmetics

Silver finished bezel / black cabinet
Solid steel black stand

LCD

17" active matrix, thin film transistor (TFT)

Pixel Pitch

0.264(H) x 0.264(V)

Max. Resolution

SXGA 1280 x 1024

Scan Frequency

Horizontal: 30kHz - 80kHz
Vertical: 50Hz - 75Hz

Mode Changes

10 preset modes
18 different user setup modes

View Angle

Horizontal: 170°
Vertical: 170°

Display Area (mm)

337.9(H) x 270.3(V)

Display Colour

16.7 million

Contrast Ratio

500:1

Brightness

250 cd/m²

Response Time (Tr+Tf)

25 ms

Compatibility

Windows 95/98/98SE/Me/NT4/2000/XP
Mac OS, Macintosh
Plug & Play - DDC 2B

Input Video Signal (Connector: 15 pin D-sub)

Analogue 0.7 Vp-p separate sync.
TTL level, positive/negative digital

AC/DC adapter:

Power built-in

Input power source:

AC 100-240V, 50-60Hz

Power management

Normal operation: < 45 W
Off/Suspend/Stand-by mode: < 3 W

Operation Environment

Temperature: 0 - 40°C
Humidity: 20% - 80%

Analogue RSB OSD

Contrast, Brightness, Phase, Pitch,
H centre, V centre, Colour, Menu position,
Reset, Backlight, Language

Control button

Power, OSD, Up / Increase,
Down / Decrease, Enter

Tilt Angle

Max. forward tilt: 5°
Max. backward tilt: 30°

Additional Features

VESA wall mount compatible
Security lock

Cabinet dimensions (W x D x H)

Gross: 550 x 245 x 536 mm
Net: 433 x 187 x 422 mm

Weight

Gross: 9.5 kg
Net: 6.8 kg

Regulation safety & EMI

FCC class B, CE, VCCI class B, UL/cUL,
TUV/GS, CB, Energy Star, TCO 95

Warranty

Three year on-site exchange

GNR Corporation Ltd

Unit 3, Newmarket Court, Kingston, Milton Keynes, MK10 0AG
Tel.: +44 (0)870 1280 880 / Fax: +44 (0)870 1280 878 / E-mail: info@gnrintl.com
www.gnrintl.com