

PF997

19" Pure Flat CRT Monitor



Specifications

Key Features

Compact designed cabinet
0.25mm dot pitch
Max. resolution 1600 x 1200 (UXGA)
Horizontal frequency 30 - 97kHz

Monitor Cosmetics

Beige colour
Tilt and swivel base

CRT

19" pure flat CRT (18" diagonal viewable size)
Anti-glare, anti-reflection & anti-static film coating

Dot Pitch

0.25mm

Resolutions

1600 x 1200 @ 75Hz
1280 x 1024 @ 85Hz
1024 x 768 @ 115Hz
800 x 600 @ 145Hz

Frequency Range

Horizontal: 30kHz - 97kHz
Vertical: 50Hz - 150Hz

Video Bandwidth

180mHz

Compatibility

Windows 95/98/98SE/Me/NT4/2000/XP
Mac OS, Macintosh
Plug & Play - DDC 2B

Input Video Signal

Video: RGB analogue (+0.7p-p, 75ohm+5%)
Sync: Separate TTL level

Input Connector

15 Pin D-sub

Input power source:

AC 100-240V, 50-60Hz

Power Consumption

Operation mode: < 130 W
Off/Suspend/Stand-by mode: < 5 W

Operation Environment

Temperature: 5° - 40°C
Humidity: 10% - 90%

On-screen Menu Controls

Brightness/contrast, H/V Position,
H/V Size, Reset, Pin cushion, Pin balance,
trapezoid, parallelogram, degauss,
rotation, convergence, multi-language,
moire, colour adjustment 9.3k/6.5k/5.5k/user)
Input freq. display, req. out of range alarm

Control button

Power, Left / Right, Up/ Down

Dimensions (W x D x H)

Gross: 541 x 570 x 522mm
Net: 448 x 465 x 434mm

Weight

Gross: 22.8kg
Net: 20.2kg

Regulation safety & EMI

FCC class B, CE, UL/cUL, MPRII
Energy Star, TCO 99 (option)

Warranty

Three year, on-site exchange

GNR Corporation Ltd

Unit 3, Newmarket Court, Kingston, Milton Keynes, MK10 0AG
Tel.: +44 (0)870 1280 880 / Fax: +44 (0)870 1280 878 / E-mail: info@gnrintl.com
www.gnrintl.com