

VL770

17" Flat Square CRT Monitor



Specifications

Key Features

Compact designed cabinet
0.27mm dot pitch
Max. resolution 1280 x 1024 (SXGA)
Horizontal frequency 30 - 72kHz

Monitor Cosmetics

Beige colour
Tilt and swivel base

CRT

17" flat square CRT (16" diagonal viewable size)
Anti-glare, anti-reflection & anti-static film coating

Dot Pitch

0.27mm

Resolutions

1280 x 1024 @ 60Hz
1024 x 768 @ 85Hz
800 x 600 @ 110Hz

Frequency Range

Horizontal: 30kHz - 72kHz
Vertical: 50Hz - 135Hz

Video Bandwidth

100mHz

Compatibility

Windows 95/98/98SE/Me/NT4/2000/XP
Mac OS, Macintosh
Plug & Play - DDC 2B

Input Video Signal

Video: RGB analogue (+0.7p-p, 75ohm+5%)
Sync: Separate TTL level

Input Connector

15 Pin D-sub

Input power source:

AC 100-240V, 50-60Hz

Power Consumption

Operation mode: < 75 W
Off/Suspend/Stand-by mode: < 5 W

Operation Environment

Temperature: 5° - 40°C
Humidity: 10% - 90%

On-screen Menu Controls

Brightness/contrast, H/V Position,
H/V Size, Reset, Pin cushion, Pin balance,
trapezoid, parallelogram, degauss,
rotation, convergence, multi-language,
moire, colour adjustment 9.3k/6.5k/5.5k/user)
Input freq. display, req. out of range alarm

Control button

Power, Left / Right, Up/ Down

Dimensions (W x D x H)

Gross: 497 x 542 x 449 mm
Net: 410 x 425 x 401 mm

Weight

Gross: 17kg
Net: 15kg

Regulation safety & EMI

FCC class B, CE, UL/cUL, MPRII
Energy Star, TCO 99 (option)

Warranty

Three year, on-site exchange

GNR Corporation Ltd

Unit 3, Newmarket Court, Kingston, Milton Keynes, MK10 0AG
Tel.: +44 (0)870 1280 880 / Fax: +44 (0)870 1280 878 / E-mail: info@gnrintl.com
www.gnrintl.com